

## Uniview kamera IPC3238ER3-DVZ 4K Dome kamera

**4K** ULTRA HDŠifra: 519  
Kategorija proizvoda: IP KAMERE  
Proizvođač: UNIVIEWCena: rsd **91.260,00**

PRO



### IPC3238ER3-DVZ 4K Dome kamera

#### 4K IR Varifokalna Dome Mrežna Kamera sa WDR-om

- Rezolucija snimanja:** 8MP (3840\*2160), Max 30fps; 2MP (1920\*1080), Max 30fps
- Čip:** 1/2.5", 8.0 megapixel, progressive scan, CMOS
- Šater:** Auto/Manual, 1 ~ 1/100000s
- Optika:** 2.8 ~ 12mm@F1.6
- Osetljivost:** 0.02Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db
- IC domet:** do 30m
- Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 1x Alarmni ulaz, 1x Alarmni izlaz, BNC izlaz, DC12V izlaz sa PoE napajanjem.
- Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
- Mrežni standardi:** ONVIF (Profile S, Profile T), API
- Kompresija:** Ultra 265, H.265, H.264, MJPEG
- Smart funkcije:** Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.
- Inteligentne indentifikacije:** Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.
- Statističke analize:** Brojanje ljudi
- Ostale Karakteristike:** 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod
- Zaštita:** IP67, IK10
- Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 8,7W
- Radna Temperatura:** -40°C ~ 60°C (-40°F ~ 140°F),
- Vlažnost:** ≤95% RH (ne kondenzujuće)
- Dimenzije (ΦxV):** Φ148 x 111.3mm, težina: 0.92kg
- Kompatibilni nosači i pribor:** TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB/WM04-B-IN