

Uniview switch IPC6854SR-X38UP-VC

Šifra: 526

Kategorija proizvoda: IP KAMERE

Proizvođač: UNIVIEW

Cena: **rsd 280.800,00**

PRO



IPC6854SR-X38UP-VC

4 MP Speed Dome AI Metadata PTZ kamera sa 38x optičkim zoom-om

-Rezolucija snimanja: 2688*1520 resolution,60fps

-Čip: 1/1.8", 4.0 megapixel, progressive scan, CMOS

-Šater: Auto/Manual, 1 ~ 1/100000s

-Optika: 5.7 ~ 216.6mm, automatski fokus

-Osetljivost: Color: 0.0005Lux (F1.3, AGC ON)0Lux with IR on, 120db WDR

-IC domet: do 250m

-PTZ komande: 16 patrola i 1024 preseta po patroli, Home pozicija.

-Interfejsi: 10/100M Base-TX Ethernet, Micro SD do 256GB, 2x Alarmna ulaza, 1 Alarmni izlaz, RS485

-Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

-Mrežni standardi: ONVIF (Profile S, Profile T), API

-Kompresija: Ultra 265, H.265, H.264, MJPEG

-Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Audio Detection, Defocus Detection, People counting, Face detection.

-Ostale Karakteristike: Optičkil Defog i Digitalni Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod, EIS (žiroskopska stabilizacija slike), Umanjuje False Alarme, Metadata (Boja automobila, da li je motocikl ili auto, kod ljudi godine, naočare da li nosi, pol osobe...)

-Zaštita: IP66

-Napajanje i potrošnja: AC 24V ±25%, DC 24V ±25%, PoE++ (IEEE 802.3bt) (IEEE802.3bt switch required), potrošnja od 16-51W

-Radna Temperatura: -40°C ~ 70°C (-22°F ~ 140°F),

-Vlažnost: ≤95% RH (ne kondenzujuće)

-Dimenzije (ΦxV): 357× 106 × 194mm (14.1" × 4.2" × 7.7")

-Kompatibilni nosači i pribor: TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-A- IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP08-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-IN